

V230 - NEW

SKID LOADERS



GEHL®

Capacities		Metric	Imperial
Operating Capacity At 50% Tipping Load		1043.26 kg	2300 lb
Operating Weight		3497 kg	7710 lb
Unladen weight		3150 kg	6945 lb
Tipping capacity		2086.53 kg	4600 lb
Weight and dimensions			
Operating Weight - Approximate		3497 kg	7710 lb
Overall Operating Height - Fully Raised	h27	4039 mm	159 in
Height to Hinge Pin - Fully Raised	h28	3086 mm	121 in
Overall Height to Top of ROPS	h17	2058 mm	81 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2312 mm	91 in
Overall length with bucket	l16	3589 mm	141 in
Dump reach - Full height	r6	826 mm	33 in
Rollback Angle at Full Height	a4	92 °	92 °
Seat to ground height	h30	978 mm	39 in
Overall width less bucket	b1	1707 mm	67 in
Ground clearance	m4	203 mm	8 in
Overall length - Less Bucket	l2	2789 mm	110 in
Clearance Radius - Front with Bucket	b18	2171 mm	85 in
Clearance Circle - Front without Bucket	b19	1308 mm	51 in
Clearance Circle - Rear	wa1	1689 mm	66 in
Performances			
Travel Speed with Two-Speed Option - Maximum		20 km/h	12 mi/h
Travel speed (unladen)		12.70 km/h	8 mi/h
Wheels			
Transmission type		Hydrostatic	Hydrostatic
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98CT-XNGL	4TNV98CT-XNGL
Engine norm		Stage V	Stage V
Gross Power (kW)		53.70 kW	54 kW
Net Power (kW)		52.70 kW	53 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm	217 ft/lbs / 1800 rpm
Number of cylinders		4	4
Engine cooling system		Water	Water
Battery		12 V	12 V
Alternator - Ampere		100 A	100 A
Starter (kW)		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		86.50 l/min	23 US gpm
Auxiliary Hydraulic Pressure		239.59 bar	3475 PSI
High-Flow Auxiliary Hydraulics - Option		114 l/min	30 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		229.25 bar	3325 PSI
Tank capacities			
Fuel tank		106 l	28 US gal
Displacement		3.30 l	0.87 US gal
Coolant system capacity		18 l	5 US gal



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend