SKID LOADERS



GEHL

Capacities		Metric	Imperial
Operating Capacity At 50% Tipping Load		1247 kg	2749 lb
Rated Operating Capacity with Optional Counterweight		1327 kg	2926 lb
Operating Weight		3774 kg	8320 lb
Jnladen weight		3426 kg	7553 lb
Tipping capacity		2495 kg	5501 lb
Weight and dimensions			
Operating Weight - Approximate		3774 kg	8320 lb
Overall Operating Height - Fully Raised	h27	4252 mm	167 in
Height to Hinge Pin – Fully Raised	h28	3277 mm	129 in
Overall Height to Top of ROPS	h17	2058 mm	81 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2489 mm	98 in
Overall length with bucket	l16	3810 mm	150 in
Dump reach - Full height	r6	830 mm	33 in
Rollback Angle at Full Height	a4	92 °	92 °
Seat to ground height	h30	978 mm	39 in
Overall width less bucket	b1	1712 mm	67 in
Ground clearance	m4	216 mm	9 in
Overall length - Less Bucket	12	3023 mm	119 in
Clearance Radius - Front with Bucket	b18	2289 mm	90 in
Clearance Circle - Front without Bucket	b19	1410 mm	56 in
Clearance Circle - Rear	wa1	1829 mm	72 in
Performances			
Fravel Speed with Two-Speed Option - Maximum		17.50 km/h	11 mi/h
Fravel speed (unladen)		11.40 km/h	7 mi/h
Wheels			·
Transmission type		Hydrostatic	Hydrostatic
Engine		,	,
Engine brand		Yanmar	Yanmar
Engine model		4TNV98CT-XNGL	4TNV98CT-XNGL
Engine norm		Stage V	Stage V
Gross Power (kW)		53.70 kW	54 kW
Net Power (kW)		52.70 kW	53 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm	217 ft/lbs / 1800 rpm
Number of cylinders		4	4
Engine cooling system		Water	Water
Battery		12 V	12 V
Alternator - Ampere		100 A	100 A
Starter (kW)		3 kW	3 kW
Hydraulics		3 KW	3 889
Standard flow - Auxiliary hydraulics		98.40 l/min	26 US gpm
Auxiliary Hydraulic Pressure		239.59 bar	3475 PSI
High-Flow Auxiliary Hydraulics – Option		126 l/min	33 US gpm
ligh-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar	33 05 gpiii 3325 PSI
Fank capacities		227.25 DUI	3323 1 31
Fuel tank		106 l	28 US gal
Reservoir Capacity Hydraulics		22.70 l	6 US gal
		3.30 l	0.87 US gal
Displacement Coolant system capacity		3.30 l 18 l	0.87 US gal 5 US gal





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend