

VT275 - NEW

TRACK LOADERS



GEHL®

Capacities		Metric	Imperial
Rated Operating Capacity		1782 kg	3929 lb
Rated Operating Capacity with Optional Counterweight		1860 kg	4101 lb
Operating Weight		4559 kg	10051 lb
Unladen weight		4145 kg	9138 lb
Weight and dimensions			
Operating Weight - Approximate		4559 kg	10051 lb
Overall Operating Height - Fully Raised	h27	4265 mm	168 in
Height to Hinge Pin - Fully Raised	h28	3289 mm	129 in
Overall Height to Top of ROPS	h17	2082 mm	82 in
Dump angle at full height	a5	42 °	42 °
Dump height	h29	2502 mm	99 in
Overall length with bucket	l16	3810 mm	150 in
Dump reach - Full height	r6	879 mm	35 in
Rollback Angle at Full Height	a4	92 °	92 °
Seat to ground height	h30	1003 mm	39 in
Overall width less bucket	b1	1803 mm	71 in
Bucket Width	e1	1880 mm	74 in
Ground clearance	m4	229 mm	9 in
Overall length - Less Bucket	l2	3023 mm	119 in
Clearance Radius - Front with Bucket	b18	2362 mm	93 in
Clearance Circle - Front without Bucket	b19	1486 mm	59 in
Clearance Circle - Rear	wa1	1753 mm	69 in
Performances			
Travel Speed with Two-Speed Option - Maximum		13.50 km/h	8 mi/h
Travel speed (unladen)		8.90 km/h	6 mi/h
Wheels			
Transmission type		Hydrostatic	Hydrostatic
Standard tyres		15.7 in - 400 mm	15.7 in - 400 mm
Engine			
Engine brand		Yanmar	Yanmar
Engine model		4TNV98CT-XNGL	4TNV98CT-XNGL
Engine norm		Stage V	Stage V
Gross Power (kW)		53.70 kW	54 kW
Net Power (kW)		52.70 kW	53 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm	217 ft/lbs / 1800 rpm
Number of cylinders		4	4
Engine cooling system		Water	Water
Battery		12 V	12 V
Alternator - Ampere		100 A	100 A
Starter (kW)		3 kW	3 kW
Hydraulics			
Standard flow - Auxiliary hydraulics		98.40 l/min	26 US gpm
Auxiliary Hydraulic Pressure		239.59 bar	3475 PSI
High-Flow Auxiliary Hydraulics - Option		126 l/min	33 US gpm
High-Flow Auxiliary Hydraulics Pressure - Option		229.25 bar	3325 PSI
Tank capacities			
Fuel tank		143.80 l	38 US gal
Reservoir Capacity Hydraulics		22.70 l	6 US gal
Coolant system capacity		18 l	5 US gal



GEHL®

Siège Social

P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095

Tel: (262) 334-9461 - Fax: (262) 338-7517

www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend